

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in this application.

1. (Currently amended) An inflatable well completion tool comprising:

a slurry source having gravel laden slurry disposed therein and flowing therethrough;

an inflatable element having an interior volume;

a particulate filter operatively coupled to interior volume of the inflatable element and having a first side disposed toward the gravel laden slurry within the slurry source and a second side disposed toward the interior volume of the inflatable element; and

wherein the inflatable element is adapted for inflation by filled with an inflating fluid obtained from filtering a gravel the gravel laden slurry using through the particulate filter and into the interior volume of the inflatable element.

2. (Original) The well completion tool of Claim 1 wherein the inflatable element is capable of movement between a deflated state and an inflated state.

3. (Currently amended) The well completion tool of Claim 2 wherein the inflatable element comprises a top end, a bottom end, ~~an interior,~~ and a passageway allowing communication of the

inflating fluid between the top end of the inflatable element and the interior of the inflatable element.

4. (Original) The well completion tool of Claim 3 wherein the passageway comprises at least one shunt tube.

5. (Original) The well completion tool of Claim 3 wherein the passageway comprises at least one alternative channel.

6. (Original) The well completion tool of Claim 3 wherein the inflatable element further comprises a passageway allowing communication of the inflating fluid between the bottom end of the inflatable element and the interior of the inflatable element.

7. (Original) The well completion tool of Claim 6 wherein the passageway comprises a check valve that restricts reverse flow.

8. (Original) The well completion tool of Claim 1 further comprising:

a first sand screen;

a second sand screen; and

wherein the inflatable element isolates the first sand screen from the second sand screen.

9. (Original) The well completion tool of Claim 1 further comprising:

a sand screen; and

wherein the inflatable element is placed below the sand screen and isolates the sand screen from the well below the inflatable element.

10. (Currently amended) An isolation packer for use in a wellbore comprising:

an inflatable element;

a passageway communicating between ~~an exterior~~ a slurry source having gravel laden slurry disposed therein and flowing therethrough and an interior of the inflatable element;

a particulate filter ~~located on~~ disposed within the passageway and having a first side disposed toward the gravel laden slurry within the slurry source and a second side disposed toward the interior volume of the inflatable element; and

wherein the inflatable element is ~~capable of being inflated by~~ filled with an inflating fluid obtained from filtering, by the particulate filter, ~~a gravel~~ gravel laden slurry ~~traveling on~~ passing through the passageway.

11. (Original) The isolation packer of Claim 10 wherein the passageway comprises at least one shunt tube.

12. (Original) The isolation packer of Claim 10 wherein the passageway comprises at least one alternative channel.

13. (Original) The isolation packer of Claim 10 further comprising:

a first sand screen;

a second sand screen; and

wherein the inflatable element isolates the first sand screen from the second sand screen.

14. (Original) The isolation packer of Claim 10 further comprising:

a lowermost sand screen; and

wherein the inflatable element is placed below the lowermost sand screen and isolates the lowermost sand screen from the well below the inflatable element.

15. (Original) The isolation packer of claim 10 wherein the passageway comprises a check valve that restricts reverse flow.

16. (Original) The isolation packer of claim 10 further comprising a tubular body attached to the inflatable element.

17. (Currently amended) A wellbore isolation device comprising:

a tubular body member having first and second segments, each segment having an exterior and a longitudinal bore extending therethrough;

a slurry source having gravel laden slurry disposed therein and flowing therethrough;

a bladder surrounding the second segment of the tubular body, the bladder having a wall, an interior, an upper end, and a lower end;

a passageway located adjacent the exterior of the first segment and extending through the wall of the bladder element;

a particulate filter ~~located on~~ disposed within the passageway and operatively coupled to the interior of the bladder, having a first side disposed toward the interior of the bladder and a second side disposed toward the slurry source; and

wherein the passageway allows a gravel laden slurry to be filtered by the particulate filter thereby producing an inflating fluid ~~which enters and expands the bladder and wherein the bladder is filled with the inflating fluid produced by filtering the gravel laden slurry.~~

18. (Original) The device of Claim 17, wherein the passageway comprises a check valve that restricts reverse flow.

19. (Original) The device of Claim 17, wherein the bladder is expandable in a radial direction.

20. (Original) The device of Claim 19, wherein the bladder is attached to the tubular body member.

21. (Original) The device of Claim 20, wherein the bladder has an upper end and a lower end, and both the upper end and the lower end are connected to the tubular body member.

22. (Original) The device of Claim 21 wherein the second tubular body segment comprises an upper packer head and a lower packer head, and the bladder upper end is connected to the upper packer head and the bladder lower end is connected to the lower packer head.

23. (Original) The device of Claim 22 wherein the passageway extends through the upper packer head and communicates between the exterior of the first segment of the tubular body member and the interior of the bladder.

24. (Original) The device of Claim 22 wherein the passageway extends through the upper and lower packer heads and communicates between the exterior of the first and second segments of the tubular body member and the interior of the bladder.

25. (Original) The device of Claim 17 wherein the passageway enables communication between the exterior of the first segment of the tubular body member and the interior of the bladder.

26. (Original) The device of Claim 17 further comprising a third segment of the tubular body member wherein the passageway enables communication between the exterior of the first and third segments with the interior of the bladder.

27. (Original) The device of Claim 17 wherein the passageway comprises a shunt tube.

28. (Original) The device of Claim 17 wherein the passage way comprises an alternative channel.



29. (Currently amended) A wellbore isolation tool comprising:  
a tubular body having a longitudinal bore therethrough and an exterior having gravel laden slurry disposed thereabout and flowing thereabout;

an expandable bladder attached to the tubular body;

a passageway providing communication between the expandable bladder and the gravel laden slurry disposed about the exterior of the tubular body;

a particulate filter communicably coupled to the expandable bladder and ~~located on~~ disposed within the passageway, the particulate filter having a first side disposed toward the gravel laden slurry and a second side disposed toward an interior of the bladder; and

wherein ~~the passageway allows a~~ gravel laden slurry ~~to be~~ is filtered by the particulate filter thereby producing an inflating fluid which enters and expands the expandable bladder.

30. (Original) The wellbore isolation tool of Claim 29 wherein the passageway comprises a check valve that restricts reverse flow.

31. (Original) The wellbore isolation tool of Claim 31 wherein the bladder has an upper end and a lower end, and both the upper end and the lower end are connected to the tubular body.

32. (Original) The wellbore isolation tool of Claim 29 wherein the passageway comprises a shunt tube.

33. (Original) The wellbore isolation tool of Claim 29 wherein the passage way comprises an alternative channel.

34. (Currently amended) An isolation packer system for use in a wellbore comprising:

a tubular body member having first, second and third segments, the first and third segments being on opposite ends of the second segment, each segment having an exterior and a longitudinal bore extending therethrough;

a bladder surrounding the second segment of the tubular body, the bladder having a wall and an interior;

a passageway located adjacent the first and third segments and extending through the wall of the bladder;

at least one particulate filter located on the passageway and in communication with the bladder; and

wherein the ~~passageway allows a gravel laden slurry to be filtered by the~~ particulate filter filters gravel laden slurry thereby producing an inflating fluid which enters and expands the bladder.

35. (Original) The system of Claim 34 wherein the passageway enables communication between the exterior of the first and third segments with the interior of the bladder.

36. (Original) The system of Claim 34 wherein during a gravel pack completion of a wellbore the passageway allows the gravel laden slurry to communicate between the exterior of the first and third segments and the at least one particulate filter.

37. (Original) The system of Claim 34 wherein the passageway comprises a check valve that restricts reverse flow.

38. (Original) The system of Claim 34 wherein the at least one particulate filter comprises a check valve that restricts reverse flow.

39. (Original) The system of Claim 34 wherein the bladder is capable of radial expansion upon being filled with the inflating fluid.

40. (Original) The system of claim 39 whereupon radial expansion the bladder forms a seal between the tubular body and the wellbore wall.

41. (Original) The system of Claim 34 wherein the passageway comprises a shunt tube.

42. (Original) The system of Claim 34 wherein the passage way comprises an alternative channel.

43. (Original) The system of Claim 34 further comprising a cup packer affixed along some portion of the wellbore wall for creating a pressure seal.

44. (Original) A method of sealing an annulus in a well, comprising the steps of:

filtering a gravel laden slurry to produce an inflating fluid;  
and  
expanding an inflatable element with the inflating fluid.

45. (Original) The method of Claim 44 further comprising the step of communicating, over a passageway, the inflating fluid between an exterior and an interior of the inflatable element.

46. (Original) The method of Claim 45 further comprising the step of restricting reverse flow of the inflating fluid on the passageway with a check valve.

47. (Original) The method of Claim 44 further comprising the step of obtaining the gravel laden slurry from a gravel packing of the well.

48. (Original) The method of Claim 44 further comprising the step of:

sealing an annulus of the well; and  
isolating a first zone from a second zone.

49. (Original) A method of completing a well comprising the steps of:

providing a sand screen completion having at least one inflatable element therein;

gravel packing at least a portion of the well with a gravel slurry;

filtering the gravel slurry with a particulate filter to produce an inflating fluid; and

inflating the inflatable element with the inflating fluid.

50-52. (Canceled)

53. (Previously presented) The method of Claim 49 further comprising the step of:

communicating between an exterior and interior of the inflatable element with a passageway.

54. (Previously presented) The method of Claim 49 further comprising the step of passing a portion of the gravel slurry through the passageway.

55. (Previously presented) The method of Claim 55 further comprising the steps of:

sealing an annulus of the well with the inflatable element;  
and

isolating a first zone from a second zone.